

# RSL-2702



*Where Quality and Value Reign*

## **FULL FEATURED TABLE TOP LAMINATOR**



### **Features & Benefits**

- **Fast** - Laminates thermal and pressure sensitive films up to 27" (685mm) wide at speeds up to 8.2' (2.5m) per minute.
- **Versatile**– Able to mount boards up to 3/16" (6mm) and laminate up to 10mil (250mic) film.
- **Flexible** -Designed for laminating, encapsulating and mounting with adjustable nip settings (max. opening 3/16"/6mm).
- **Easy To Use** - Soft touch digital keypad allows easy operation and function control of temperature, speed and stored programs.
- **Convenient**– Pull out film shafts and drop down idler all in a tabletop roll laminator designed for a small working area.

#### **ROYAL SOVEREIGN INTERNATIONAL, INC.**

2 Volvo Drive, Rockleigh, NJ 07647

Tel: (800) 397-1025 (201) 750-1020 Fax: (201) 750-1022

#### **ROYAL SOVEREIGN CANADA**

1025 Westport Crescent, Mississauga, Ontario L5T 1E8

Tel: (905) 461-1095 Fax: (905) 461-1096

**Website: [www.royalsovereign.com](http://www.royalsovereign.com) Email: [info-ca@royalsovereign.com](mailto:info-ca@royalsovereign.com)**

## Royal Sovereign Canada, Inc.

### Specifications

| <b>Model</b>                     | <b>RSL-2702</b>                                |
|----------------------------------|--|
| Power supply                     | AC120V / 60Hz                                  |
| Power consumption                | 1500W  |
| Max laminating width             | 27 (in) / 685 (mm)                             |
| Max laminating speed             | 8.2 (ft/min) / 2.5 (m/min)                     |
| Film thickness                   | 1~10 (mil) / 25~250 (mic)*                     |
| Film Core Size                   | Auto grip 2.25" and 3"                         |
| Max film core diameter           | 7.9"   |
| Ready time                       | 10 min   |
| Heating method                   | Hot Rollers                                    |
| Driving motor                    | DC geared motor                                |
| Temperature control              | Digital 302°F (150°C)                          |
| Speed control                    | Digital (9 settings)                           |
| Cooling system                   | 2 fans   |
| Transport type                   | 4 Roller                                       |
| Auto Off/Standby                 | Yes  |
| Cross cutter                     | Yes  |
| Document guides                  | Yes  |
| Hot lamination                   | Yes  |
| Cold lamination                  | Yes  |
| Mounting/foam board              | Yes 3/16" (6mm)                                |
| Reverse                          | Yes  |
| Unit weight                      | 124 (lbs) / 56 (kg)                            |
| Unit dimensions<br>(W x D x H)   | 38 x 21.5 x 18.5 (in)<br>970 x 540 x 470 (mm)  |
| Carton weight                    | 157 (lbs) / 71 (kg)                            |
| Carton dimensions<br>(W x D x H) | 44.5 x 24 x 23.5 (in)<br>1130 x 740 x 600 (mm) |
| Warranty                         | 1 year parts & labor (Rollers 6 months)        |

\*1-10 mil Royal Sovereign Films. Other Manufactures May Vary